



SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 FBR

AVAILABLE IN


NOIR 20578 9300 B

FLEMISH BRONZE 20578 9300 FBR

FLEMISH GOLD 20578 9300 FG

COULEUR OR 20578 9300 GC

BLANC 20578 9300 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.5
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 36,4-50,3W / CRI>90 (R9: 59) / 3000K / 5022-6665lm
SDMC	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	6665lm // 50,3W // 132lm/W
LED TECHNICS (LUMINAIRE)	2951lm // 57,8W // 51lm/W

Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM
SUPERLOOP POWERBOX H 900mA
SUPERLOOP POWERBOX H 1200mA

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTA LIGHT


SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 FBR

For detailed installation instructions, please consult the manual : [20578_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Power box


of Fixtures

web2print_power_supply_info_box		Min current Max current	
300 Ø80	<u>321 55 312 ED1 B</u>	SUPERLOOP POWERBOX H8 1200mA DIM1 B	1
Dimtype: 1 à 10 V			
	<u>321 55 312 ED1 W</u>	SUPERLOOP POWERBOX H8 1200mA DIM1 W	1
300 Ø90	<u>20548 0015 B</u>	SUPERLOOP POWERBOX H9 900mA DIM5 B	1
Dimtype: DALI			

DELTA LIGHT

SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 FBR




	<u>20548 0015 W</u>	SUPERLOOP POWERBOX H9 900mA DIM5 W	1	☐
	<u>20548 0025 B</u>	SUPERLOOP POWERBOX H9 1200mA DIM5 B	1	☐
	Dimtype: DALI			
	<u>20548 0025 W</u>	SUPERLOOP POWERBOX H9 1200mA DIM5 W	1	☐

les alimentations led



of Fixtures

 web2print_power_supply_info_box

Min current | Max current

	<u>300 90 129</u>	LED POWER SUPPLY 900mA-DC / 60W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 84			
	<u>300 90 130</u>	LED POWER SUPPLY 1200mA-DC / 60W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 95			
	<u>300 90 132</u>	LED POWER SUPPLY 1200mA-DC / 70W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 80			




les sets pour recouvrement plafond

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO		☐
	<u>204 00 62 B</u>	COVERSET R 62 B		☐
	<u>204 00 62 W</u>	COVERSET R 62 W		☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO		☐

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 FBR

	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 FBR

les accessoires de suspension

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

les accessoires pour connexions électriques

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: