



OONO W



There is more to the sophisticated Oono than just its gentle embracing glow. Built in first instance as a family of exterior products, Oono is a family of dualities. It combines elegant looks with a warm diffused light effect. It couples the sturdy look of metal with the pureness of glass. It unifies exterior and interior, as the range offers IP-rated solutions for outdoor with straightforward surface mounted and pendant luminaires for indoors. It unites a play of straight lines with perfect circular shapes. It merges black and white, by adding a touch of gold. It brings together the shimmer of dusk with the fresh start of dawn.

Specification	
Adjustability:	Fixed
Rating:	IP54

Performance	S	M	L
LED Maintenance:	L90>50,000h		
McAdam Step:	1		
CRI:	90		
*SP:	10W	14W	20W

Delivered Lumens	2700K	3000K
Oono S:	572Lm	599Lm
Oono M:	740Lm	773Lm
Oono L:	1064Lm	1113Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: ONWS-SP30FX-B-MKINCD8-120

Luminaire	Size	Power*	CCT	Function	Finish	Style	Application	Controls***
ONW OONO (Wall)	S 150mm / 5 ¹⁵ / ₁₆ "	SP Standard Power	27 2700K	FI Fixed Wall, Interior Use	GM Gold Marbled	MK Surface Canopy with mud kit over 4" junction box	INC Integral Power Supply	D8-120 FE ELV dim 120V ND-120 ^(1,2) Non-dim 120V
	M 200mm / 7 ⁷ / ₈ "		30 3000K		W White			
	L⁽¹⁾ 300mm / 11 ¹³ / ₁₆ "			FX Fixed Wall, Exterior Use	A Alu Grey B Black FBRX Flemish Bronze N Anthracite			

¹ Size L not available in Finish GM and Controls ND-120.

² Controls ND-120 only available with Size L.

*** Contact factory for Dali, DMX, or other dimming options


Related Products

Oono F, Oono P




Finish Options

OONO W S



ALU GREY




BLACK



FLEMISH BRONZE



GOLD MARBLED




ANTHRACITE




WHITE

OONO W M



ALU GREY



BLACK



FLEMISH BRONZE



GOLD MARBLED




ANTHRACITE



WHITE

OONO W L



ALU GREY



BLACK



FLEMISH BRONZE




ANTHRACITE




WHITE

Photometric Data


OONO W S



OONO W M



OONO W L



Driver Options

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥80
- THD @ Full Load <5%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.