



## SOLI - 52 93030 MDL

### REFERENCE



27112 9340 B

### AVAILABLE IN

**BLACK** 27112 9340 B

**GOLD COLOURED** 27112 9340 GC

**WHITE** 27112 9340 W



[View on website](#)



### General info

|                           |                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                      |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                                              |
| <b>INGRESS PROTECTION</b> | IP20                                                                                        |
| <b>WEIGHT (KG)</b>        | 0.4                                                                                         |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 360° rotatable                                                         |
| <b>INFORMATION</b>        | REFLECTOR FL-30°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 20° & 45° available |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC, LCA                      |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 10,3W / CRI>90 (R9: 52) / 3000K / 128lm |
| <b>TM-30 VALUES</b>                | Rf: 90 / Rg: 99                                   |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 30°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 128lm // 10,3W // 125lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 817lm // 11,8W // 69lm/W                          |

### Requirements

SPY 52 TUBE  
LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

HONEYCOMB 42  
SPREAD LENS 42  
LINEAR SPREAD LENS 42  
SOFTENING LENS 42  
GLASS SBL 42

For detailed installation instructions, please consult the manual : [27112\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

16


Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

8


Dimtype: non-dimmable

Cutout dimension (mm): 40

# DELTALIGHT

## SOLI - 52 93030 MDL

27112 9340 B




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

16 ☐

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**

### Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B

☐




**19810 0020** LINEAR SPREAD LENS 42

☐




**19810 0030** SPREAD LENS 42

☐




**19810 0040** SOFTENING LENS 42

☐



**19810 0050** GLASS SBL 42


☐



**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

☐

### Finish your product



**19810 0100 B** SPY 52 TUBE B

☐

**19810 0100 FBR** SPY 52 TUBE FBR

☐

# DELTALIGHT

## SOLI - 52 93030 MDL



27112 9340 B

|                      |                |                          |
|----------------------|----------------|--------------------------|
| <b>19810 0100 FG</b> | SPY 52 TUBE FG | <input type="checkbox"/> |
| <b>19810 0100 GC</b> | SPY 52 TUBE GC | <input type="checkbox"/> |
| <b>19810 0100 W</b>  | SPY 52 TUBE W  | <input type="checkbox"/> |

### Replaceable reflector / lens

|                                                                                    |                                        |                          |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
|    | <b>19810 0180</b> SPY 52 REFLECTOR 20° | <input type="checkbox"/> |
|   | <b>19810 0190</b> SPY 52 REFLECTOR 45° | <input type="checkbox"/> |
|  | <b>19810 0240</b> SPY 52 REFLECTOR 30° | <input type="checkbox"/> |

## COMPATIBLE COMPOSABLES

| SOLISCAPE profile                                                                                                         | Available Colours                                                                                                                                                           |
|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>27111 0020</b> SOLI - PROFILE 2m |   |
| <br><b>27111 0030</b> SOLI - PROFILE 3m |   |

Notes: