
DELTALIGHT




# FRAX M 92714 HONEYCOMB

**REFERENCE** 26011 9220 A

AVAILABLE IN
**ALU GREY** 26011 9220 A
**FLEMISH BRONZE OUTDOOR** 26011 9220 FBRX
**ANTHRACITE** 26011 9220 N




View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Surface mounted,Wall Surface mounted |
| **INGRESS PROTECTION** | IP65 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK08 |
| **WEIGHT (KG)** | 2.4 |
| **ADJUSTABILITY** | 0° to 120° swiveling, 360° rotatable |
| **INFORMATION** | 9 x LENS SP-14°<br>INCL.LED POWER SUPPLY 900mA-DC<br>INCL.HONEYCOMB |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | non-dimmable |
| **ENERGY CLASS** | F |
| **CERTIFICATES** | EPD, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2423lm |
| **TM-30 VALUES** | Rf: 91 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 14° |
| **LED TECHNICS (LIGHT SOURCE)** | 2423lm // 23,4W // 103lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1526lm // 26,9W // 57lm/W |

**Options**

FRAX ANTI VANDAL SCREWS

**Accessories**

FRAX M KAP

For detailed installation instructions, please consult the manual : **26011_XX20_HAND.pdf**


DELTALIGHT

# FRAX M 92714 HONEYCOMB

26011 9220 A


## FINISH YOUR SPECIFICATION

### Light altering devices




**26070 0020 N** FRAX M KAP N ☐

### Other



**26070 0030** FRAX ANTI VANDAL SCREWS 5 PCS ☐

Notes: