




M20/M26H - SPY 66 92745 MDL

23327 9230 W

AVAILABLE IN
BLACK 23327 9230 B
WHITE 23327 9230 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 30° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 60) / 2700K / 2688lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2688lm // 25W // 108lm/W
LED TECHNICS (LUMINAIRE)	1845lm // 28,8W // 64lm/W

Remarks
Take a look at our MAGNETIC PROFILES movie

Requirements
SPY 66 TUBE LED POWER SUPPLY 48V-DC

Options
DIMMABLE MODULATOR

Accessories
HONEYCOMB 57

DELTALIGHT

M20/M26H - SPY 66 92745 MDL

23327 9230 W

For detailed installation instructions, please consult the manual : [23327_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

6


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

6

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

6


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN




3

Dimtype: non-dimmable

DELTALIGHT

M20/M26H - SPY 66 92745 MDL


23327 9230 W

	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	8	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	3	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	7	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			

Light altering devices

	24611 0150 B HONEYCOMB 57 SINGLE USE B		☐
--	---	--	--------------------------

Finish your product

	24611 0100 B SPY 66 TUBE B		☐
	24611 0100 FBR SPY 66 TUBE FBR		☐
	24611 0100 FG SPY 66 TUBE FG		☐
	24611 0100 GC SPY 66 TUBE GC		☐
	24611 0100 W SPY 66 TUBE W		☐

DELTALIGHT

M20/M26H - SPY 66 92745 MDL

23327 9230 W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°



24611 0230 SPY 66 REFLECTOR 30°




24611 0240 SPY 66 REFLECTOR 45°




COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



DELTALIGHT

M20/M26H - SPY 66 92745 MDL

23327 9230 W



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: