
DELTALIGHT




# M20/M26H - SPY 66 92745 MDL

**REFERENCE** 23327 9230 W

AVAILABLE IN
**BLACK** 23327 9230 B
**WHITE** 23327 9230 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.6 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR WFL-45°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 18° & 30° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 25W / CRI>90 (R9: 60) / 2700K / 2688lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 45° |
| **LED TECHNICS (LIGHT SOURCE)** | 2688lm // 25W // 108lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1845lm // 28,8W // 64lm/W |

## Remarks

**Take a look at our MAGNETIC PROFILES movie**

## Requirements

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

## Options

DIMMABLE MODULATOR

## Accessories

HONEYCOMB 57

DELTALIGHT

# M20/M26H - SPY 66 92745 MDL

23327 9230 W

For detailed installation instructions, please consult the manual : **23327_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### Current supply

**# of Fixtures**

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**21032 0030** SMART 48 MODULATOR PLUG-IN WD — 6


**Dimtype: WDL = wireless dimmable**

### SMART 48

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 6

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 6


**Dimtype: WDL = wireless dimmable**

### LED power supplies

**# of Fixtures**

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 3

**Dimtype: non-dimmable**


# M20/M26H - SPY 66 92745 MDL

23327 9230 W




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 8


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 3

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 7

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**

## Light altering devices




**24611 0150 B** HONEYCOMB 57 SINGLE USE B

## Finish your product




**24611 0100 B** SPY 66 TUBE B

**24611 0100 FBR** SPY 66 TUBE FBR

**24611 0100 FG** SPY 66 TUBE FG

**24611 0100 GC** SPY 66 TUBE GC

**24611 0100 W** SPY 66 TUBE W

DELTALIGHT

# M20/M26H - SPY 66 92745 MDL

23327 9230 W

## Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°



**24611 0230** SPY 66 REFLECTOR 30°




**24611 0240** SPY 66 REFLECTOR 45°


## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H profile


Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m

### SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE

DELTALIGHT

# M20/M26H - SPY 66 92745 MDL

23327 9230 W





**23397 0020** SPM20 ST - PROFILE 2m





**23397 0030** SPM20 ST - PROFILE 3m


| SPLITLINE M20 profile | Available Colours |
|---|---|





**420 20 10 00** SPM20 - PROFILE 1m




**420 20 20 00** SPM20 - PROFILE 2m




**420 20 30 00** SPM20 - PROFILE 3m




**23301 0000** SPM20 - PROFILE B

Notes: