
DELTALIGHT




# OBIN ON 92724 DIM8

**REFERENCE** 30511 9228 B

AVAILABLE IN
**BLACK** 30511 9228 B
**BRUSHED ALU** 30511 9228 BRA
**BRUSHED ANTHRACITE** 30511 9228 BRAT
**BRUSHED BROWN BRONZE** 30511 9228 BRBB
**BRUSHED GOLD** 30511 9228 BRG
**BRUSHED OLD BRONZE** 30511 9228 BROB
**CREAM** 30511 9228 CR
**WHITE** 30511 9228 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Surface mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 45° swiveling, 360° rotatable |
| **INFORMATION** | LENS FL-24°<br>INCL.DIMMABLE POWER SUPPLY |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | mains (phase cut-off) |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 24° |
| **LED TECHNICS (LIGHT SOURCE)** | 1458lm // 11,6W // 125lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1217lm // 13,3W // 91lm/W |

**Requirements**

SPY 90 TUBE

**Accessories**

HONEYCOMB 75

DELTALIGHT


# OBIN ON 92724 DIM8

30511 9228 B

For detailed installation instructions, please consult the manual : **30511_XXX8_HAND.pdf**


## FINISH YOUR SPECIFICATION

### Light altering devices




**19810 0110 B** HONEYCOMB 75 SINGLE USE B ☐

### Finish your product




**19810 0170 B** SPY 90 TUBE B ☐

**19810 0170 CR** SPY 90 TUBE CR ☐

**19810 0170 DC** SPY 90 TUBE DC ☐

**19810 0170 FBR** SPY 90 TUBE FBR ☐

**19810 0170 FG** SPY 90 TUBE FG ☐

**19810 0170 GC** SPY 90 TUBE GC ☐

**19810 0170 PB** SPY 90 TUBE PB ☐

**19810 0170 W** SPY 90 TUBE W ☐

Notes:

## OBIN ON 92724 DIM8

30511 9228 B