



M20/M26H - OBIN 93024 DIM5

30514 9325 BRA

AVAILABLE IN

BLACK 30514 9325 B

BRUSHED ALU 30514 9325 BRA

BRUSHED ANTHRACITE 30514 9325 BRAT


BRUSHED BROWN BRONZE 30514 9325 BRBB

BRUSHED GOLD 30514 9325 BRG

BRUSHED OLD BRONZE 30514 9325 BROB

CREAM 30514 9325 CR

WHITE 30514 9325 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-24° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1272lm // 13,3W // 95lm/W

Requirements

SPY 90 TUBE

LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 75

M20/M26H - OBIN 93024 DIM5

30514 9325 BRA

For detailed installation instructions, please consult the manual : [30514_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	7	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	14	
3017298 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	7	
3022392 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	14	
Light altering devices		
13075 19810 0110 B HONEYCOMB 75 SINGLE USE B		

DELTALIGHT


M20/M26H - OBIN 93024 DIM5

30514 9325 BRA

Finish your product

	19810 0170 B	SPY 90 TUBE B	☐
	19810 0170 CR	SPY 90 TUBE CR	☐
	19810 0170 DC	SPY 90 TUBE DC	☐
	19810 0170 FBR	SPY 90 TUBE FBR	☐
	19810 0170 FG	SPY 90 TUBE FG	☐
	19810 0170 GC	SPY 90 TUBE GC	☐
	19810 0170 PB	SPY 90 TUBE PB	☐
	19810 0170 W	SPY 90 TUBE W	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL		Available Colours
	30411 9205 SHIFTLINE M26H + SBL 2m DIM5	☒ ☐
	30411 9305 SHIFTLINE M26H + SBL 2m DIM5	☒ ☐
	30412 9205 SHIFTLINE M26H + SBL 3m DIM5	☒ ☐


DELTALIGHT

M20/M26H - OBIN 93024 DIM5


30514 9325 BRA



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5




SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m



DELTALIGHT

M20/M26H - OBIN 93024 DIM5

30514 9325 BRA




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: