



## M26L - BOXY L A TW 96545 DIM5

10743 9035 B-FG



AVAILABLE IN

**BLACK-BLACK** 10743 9035 B-B

**BLACK-FLEMISH BRONZE** 10743 9035 B-FBR

**BLACK-FLEMISH GOLD** 10743 9035 B-FG

**WHITE-WHITE** 10743 9035 W-W



[View on website](#)



### General info

|                           |                                                                       |
|---------------------------|-----------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                        |
| <b>INGRESS PROTECTION</b> | IP20                                                                  |
| <b>WEIGHT (KG)</b>        | 0.4                                                                   |
| <b>ADJUSTABILITY</b>      | non adjustable                                                        |
| <b>INFORMATION</b>        | REFLECTOR WFL-45°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                   |
| <b>LIGHTSOURCE</b>                 | LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                      |
| <b>SDCM</b>                        | SDCM2                                                 |
| <b>RISKGROUP</b>                   | RG1                                                   |
| <b>LM80</b>                        | L90B10 > 50000                                        |
| <b>BEAMANGLE</b>                   | 45°                                                   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1087lm // 9W // 121lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 843lm // 10,4W // 81lm/W                              |

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

LED POWER SUPPLY 48V-DC

### Accessories

BOXY HONEYCOMB  
BOXY SOFTENING LENS  
BOXY GLASS SBL

# DELTALIGHT

## M26L - BOXY L A TW 96545 DIM5

10743 9035 B-FG

For detailed installation instructions, please consult the manual : [10743\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

9


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

23

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

9

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

19

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



Ø40



Ø45

**251 70 03 01 B** BOXY HONEYCOMB B

**251 70 03 01 W** BOXY HONEYCOMB W



Ø40



Ø45

**251 70 03 04 B** BOXY SOFTENING LENS B





# DELTALIGHT

## M26L - BOXY L A TW 96545 DIM5

10743 9035 B-FG

|                                                                                   |                                             |                          |
|-----------------------------------------------------------------------------------|---------------------------------------------|--------------------------|
|  | <b>251 70 03 04 W</b> BOXY SOFTENING LENS W | <input type="checkbox"/> |
|  | <b>251 70 03 05 B</b> BOXY GLASS SBL B      | <input type="checkbox"/> |
|                                                                                   | <b>251 70 03 05 W</b> BOXY GLASS SBL W      | <input type="checkbox"/> |

### COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)                                    | Available Colours                                                                     |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|    |    |
|  |  |
|  |  |
|  |  |

Notes: