





## INFORM 40 SQ 360 DOWN-UP 93063 DIM5

30735 9335 W-B

AVAILABLE IN

**BLACK-BLACK** 30735 9335 B-B

**WHITE-BLACK** 30735 9335 W-B



[View on website](#)



| General info                |                                                                                                                                                                                                                                                                  |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                                                                                                                                                                                           |
| INSTALLATION                | Ceiling Suspended                                                                                                                                                                                                                                                |
| INGRESS PROTECTION          | IP20                                                                                                                                                                                                                                                             |
| WEIGHT (KG)                 | 5.9                                                                                                                                                                                                                                                              |
| ADJUSTABILITY               | non adjustable                                                                                                                                                                                                                                                   |
| INFORMATION                 | INCL.DIMMABLE LED POWER SUPPLY (DALI DT6)<br>Power selection to be set on driver<br>DALI DT6 : DOWN & UP on separate channels<br>INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m<br>INCL.1 x CABLE 5 x 0,75mm <sup>2</sup> 1,6m                                      |
| Electrical info             |                                                                                                                                                                                                                                                                  |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                                                                                                                                                                                             |
| CLASS                       | I                                                                                                                                                                                                                                                                |
| POWER SUPPLY                | YES                                                                                                                                                                                                                                                              |
| DIM TYPE                    | DALI                                                                                                                                                                                                                                                             |
| ENERGY CLASS                | E                                                                                                                                                                                                                                                                |
| Lightsource info            |                                                                                                                                                                                                                                                                  |
| LIGHTSOURCE NAME            | LED                                                                                                                                                                                                                                                              |
| LIGHTSOURCE                 | DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm<br>UP (HO): LED cluster 60,5W / CRI>90 (R9: 50) / 3000K / 8736lm<br>Or<br>DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm<br>UP: LED cluster 41,8W / CRI>90 (R9: 50) / 3000K / 6464lm |
| TM-30 VALUES                | Rf: 92 / Rg: 100<br>DOWN: rf: 92 / Rg: 100<br>UP: rf: 92 / Rg: 100                                                                                                                                                                                               |
| SDCM                        | SDCM3                                                                                                                                                                                                                                                            |
| RISKGROUP                   | RG1                                                                                                                                                                                                                                                              |
| LM80                        | L80 > 60000                                                                                                                                                                                                                                                      |
| BEAMANGLE                   | 63°                                                                                                                                                                                                                                                              |
| LED TECHNICS (LIGHT SOURCE) | DOWN (HO): 6989lm // 48,4W // 145lm/W<br>UP (HO): 8736lm // 60,5W // 145lm/W<br>Or<br>DOWN: 5069lm // 32,6W // 155lm/W<br>UP: 6464lm // 41,8W // 155lm/W                                                                                                         |
| LED TECHNICS (LUMINAIRE)    | DOWN (HO): 4836lm // 55,7W // 87lm/W<br>UP (HO): 5753lm // 69,6W // 83lm/W<br>Or<br>DOWN: 3507lm // 37,5W // 94lm/W<br>UP: 4257lm // 48,1W // 89lm/W                                                                                                             |

# DELTALIGHT

## INFORM 40 SQ 360 DOWN-UP 93063 DIM5

30735 9335 W-B

Options

---


CABLE BASE R/S

For detailed installation instructions, please consult the manual : [30735\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

---



Ø57  
41

**203 99 55 ANO** CABLE BASE R ANO

☐

**203 99 55 B** CABLE BASE R B

☐

**203 99 55 W** CABLE BASE R W

☐



57 57  
41

**203 99 56 ANO** CABLE BASE S ANO

☐

**203 99 56 B** CABLE BASE S B

☐

**203 99 56 W** CABLE BASE S W

☐

Notes: