DELTALIGHT



MULTINOVA 30 930

REFERENCE 27911 9300 GC

AVAILABLE IN
BLACK 27911 9300 B
GOLD COLOURED 27911 9300 GC
WHITE 27911 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed,Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY - 2 power settings

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	HO: LED cluster 14,9W / CRI>90 (R9: 68) / 3000K / 2174lm Or LED cluster 9,8W / CRI>90 (R9: 68) / 3000K / 1358lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	HO: 2174lm // 14,9W // 146lm/W Or 1358lm // 9,8W // 139lm/W
LED TECHNICS (LUMINAIRE)	HO: 1580lm // 17W // 92lm/W Or 987lm // 11W // 88lm/W

Options

MULTINOVA 30 SUSPENSION SET
MULTINOVA 30 RECESSED KIT

For detailed installation instructions, please consult the manual : **27911_XXX0_HAND.pdf**

DELTALIGHT

MULTINOVA 30 930

27911 9300 GC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Plasterboard**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Stucanet**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Concrete + plaster**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Lintel + plaster**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Hollow-core slab + plaster**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required

FINISH YOUR SPECIFICATION

Recessed kits



27910 0050 MULTINOVA 30 RECESSED KIT ☐



Cutout dimension (mm): 341

Suspension parts



27910 0020 B MULTINOVA 30 SUSPENSION SET 5x0,75 3m B ☐

27910 0020 W MULTINOVA 30 SUSPENSION SET 5x0,75 3m W ☐

Notes:

MULTINOVA 30 930

27911 9300 GC