





M26L - SPY 39 WALLWASH SOFT 930 MDL

23435 9000 BRA

AVAILABLE IN

BLACK 23435 9000 B
BRUSHED ALU 23435 9000 BRA
BRUSHED ANTHRACITE 23435 9000 BRAT
BRUSHED COPPER 23435 9000 BRCU
BRUSHED GOLD 23435 9000 BRG
BRUSHED OLD BRONZE 23435 9000 BROB
FLEMISH BRONZE 23435 9000 FBR
FLEMISH GOLD 23435 9000 FG
GOLD COLOURED 23435 9000 GC
WHITE 23435 9000 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	WALLWASH LENS EXCL LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	341lm // 6,9W // 49lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M26L - SPY 39 WALLWASH SOFT 930 MDL

23435 9000 BRA

For detailed installation instructions, please consult the manual : [23435_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply		# of Fixtures		
		Min current Max current		
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.				
16 39 190 21032 0030 SMART 48 MODULATOR PLUG-IN WD Dimtype: WDL = wireless dimmable	16			
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.				
300 90 011 SMART 48 MODULATOR DIM9 Dimtype: 1-10V or DALI or push button			16	
300 90 012 SMART 48 MODULATOR WD Dimtype: WDL = wireless dimmable			16	
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.				
300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable			8	

DELTALIGHT

M26L - SPY 39 WALLWASH SOFT 930 MDL





23435 9000 BRA

	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours

	23358 0000 SLM26L - PROFILE	
	23358 0010 SLM26L - PROFILE 1m	
	23358 0020 SLM26L - PROFILE 2m	
	23358 0030 SLM26L - PROFILE 3m	

Notes: