



## MULTINOVA 55 DOWN-UP TW 930 DIM5



28020 9005 GC

AVAILABLE IN

**BLACK** 28020 9005 B

**GOLD COLOURED** 28020 9005 GC

**WHITE** 28020 9005 W



[View on website](#)



### General info

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                     |
| <b>INSTALLATION</b>       | Ceiling Suspended                                          |
| <b>INGRESS PROTECTION</b> | IP20                                                       |
| <b>WEIGHT (KG)</b>        | 4.6                                                        |
| <b>ADJUSTABILITY</b>      | non adjustable                                             |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY - DALI (DT8) |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | DALI               |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, EPD, RCM |

### Lightsource info

|                                    |                                                                                                                                                                                                                                                                                                        |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                                                                                                                                                                                                    |
| <b>LIGHTSOURCE</b>                 | DOWN @ 2700K: LED cluster 29,1W / CRI>90 (R9: 63) / 2700K-6500K / 419lm<br>UP @ 2700K: LED cluster 4,3W / CRI>90 (R9: 63) / 2700K-6500K / 62lm<br>Or<br>DOWN @ 6500K: LED cluster 29,2W / CRI>90 (R9: 81) / 2700K-6500K / 446lm<br>UP @ 6500K: LED cluster 4,3W / CRI>90 (R9: 81) / 2700K-6500K / 66lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                                                                                                                                                                                                  |
| <b>RISKGROUP</b>                   | RG0                                                                                                                                                                                                                                                                                                    |
| <b>LM80</b>                        | L70 > 60000                                                                                                                                                                                                                                                                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN @ 2700K: 419lm // 29,1W // 144lm/W<br>UP @ 2700K: 62lm // 4,3W // 144lm/W<br>Or<br>DOWN @ 6500K: 446lm // 29,2W // 153lm/W<br>UP @ 6500K: 66lm // 4,3W // 153lm/W                                                                                                                                 |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN @ 2700K: 3378lm // 33,5W // 101lm/W<br>UP @ 2700K: 588lm // 4,9W // 119lm/W<br>Or<br>DOWN @ 6500K: 3598lm // 33,6W // 107lm/W<br>UP @ 6500K: 626lm // 4,9W // 127lm/W                                                                                                                             |

### Options

MULTINOVA 55 SUSPENSION SET  
MULTINOVA ROD SUSPENSION

# DELTALIGHT



## MULTINOVA 55 DOWN-UP TW 930 DIM5

28020 9005 GC

For detailed installation instructions, please consult the manual : [28020\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Suspension parts

|                                                                                     |                                                             |                          |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------|--------------------------|
|    | <b>27910 0010 B</b> MULTINOVA 55 SUSPENSION SET 5x0,75 3m B | <input type="checkbox"/> |
|                                                                                     | <b>27910 0010 W</b> MULTINOVA 55 SUSPENSION SET 5x0,75 3m W | <input type="checkbox"/> |
|   | <b>27910 0030 B</b> MULTINOVA 55 ROD SUSPENSION 0,4m B      | <input type="checkbox"/> |
|                                                                                     | <b>27910 0030 W</b> MULTINOVA 55 ROD SUSPENSION 0,4m W      | <input type="checkbox"/> |
|  | <b>27910 0040 B</b> MULTINOVA 55 ROD SUSPENSION 0,8m B      | <input type="checkbox"/> |
|                                                                                     | <b>27910 0040 W</b> MULTINOVA 55 ROD SUSPENSION 0,8m W      | <input type="checkbox"/> |

Notes: