DELTALIGHT



# M20/M26H - OBIN 93024 DIM5

**REFERENCE** 30514 9325 W

AVAILABLE IN
**BLACK** 30514 9325 B
**BRUSHED ALU** 30514 9325 BRA
**BRUSHED ANTHRACITE** 30514 9325 BRAT
**BRUSHED BROWN BRONZE** 30514 9325 BRBB
**BRUSHED GOLD** 30514 9325 BRG
**BRUSHED OLD BRONZE** 30514 9325 BROB
**CREAM** 30514 9325 CR
**WHITE** 30514 9325 W







View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 45° swiveling, 360° rotatable |
| **INFORMATION** | LENS FL-24°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 24° |
| **LED TECHNICS (LIGHT SOURCE)** | 1524lm // 11,6W // 131lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1272lm // 13W // 95lm/W |

## Requirements

SPY 90 TUBE
LED POWER SUPPLY 48V-DC

## Accessories

HONEYCOMB 75

DELTALIGHT

# M20/M26H - OBIN 93024 DIM5

30514 9325 W

For detailed installation instructions, please consult the manual : **30514_XXX5_HAND.pdf**

## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 7

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 14

**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 7

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 14

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

### Light altering devices




**19810 0110 B** HONEYCOMB 75 SINGLE USE B

DELTALIGHT

# M20/M26H - OBIN 93024 DIM5

30514 9325 W

## Finish your product




**19810 0170 B** SPY 90 TUBE B

**19810 0170 CR** SPY 90 TUBE CR

**19810 0170 DC** SPY 90 TUBE DC

**19810 0170 FBR** SPY 90 TUBE FBR

**19810 0170 FG** SPY 90 TUBE FG

**19810 0170 GC** SPY 90 TUBE GC

**19810 0170 PB** SPY 90 TUBE PB

**19810 0170 W** SPY 90 TUBE W

## COMPATIBLE COMPOSABLES

| SHIFTLINE M26H + SBL | Available Colours |
|---|---|
|  **30411 9205** SHIFTLINE M26H + SBL 2m DIM5 | |
|  **30411 9305** SHIFTLINE M26H + SBL 2m DIM5 | |
|  **30412 9205** SHIFTLINE M26H + SBL 3m DIM5 | |

DELTALIGHT

# M20/M26H - OBIN 93024 DIM5

30514 9325 W



**30412 9305** SHIFTLINE M26H + SBL 3m DIM5



**30413 9205** SHIFTLINE M26H + SBL 4m DIM5



**30413 9305** SHIFTLINE M26H + SBL 4m DIM5

## SHIFTLINE M26H profile — Available Colours



**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m

## SPLITLINE M20 ST profile — Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m

DELTALIGHT

# M20/M26H - OBIN 93024 DIM5

30514 9325 W




**23397 0030** SPM20 ST - PROFILE 3m

| SPLITLINE M20 profile | Available Colours |
|---|---|
|  **420 20 10 00** SPM20 - PROFILE 1m | |
|  **420 20 20 00** SPM20 - PROFILE 2m | |
|  **420 20 30 00** SPM20 - PROFILE 3m | |
|  **23301 0000** SPM20 - PROFILE B | |



Notes: