
DELTALIGHT




OBIN ON 92724 DIM8

REFERENCE 30511 9228 W

AVAILABLE IN
BLACK 30511 9228 B
BRUSHED ALU 30511 9228 BRA
BRUSHED ANTHRACITE 30511 9228 BRAT
BRUSHED BROWN BRONZE 30511 9228 BRBB
BRUSHED GOLD 30511 9228 BRG
BRUSHED OLD BRONZE 30511 9228 BROB
CREAM 30511 9228 CR
WHITE 30511 9228 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-24° INCL.DIMMABLE POWER SUPPLY

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	1458lm // 11,6W // 125lm/W
LED TECHNICS (LUMINAIRE)	1217lm // 13W // 91lm/W

Requirements

SPY 90 TUBE

Accessories

HONEYCOMB 75

DELTALIGHT


OBIN ON 92724 DIM8

30511 9228 W

For detailed installation instructions, please consult the manual : **30511_XXX8_HAND.pdf**


FINISH YOUR SPECIFICATION

Light altering devices



19810 0110 B HONEYCOMB 75 SINGLE USE B ☐

Finish your product



19810 0170 B SPY 90 TUBE B ☐

19810 0170 CR SPY 90 TUBE CR ☐

19810 0170 DC SPY 90 TUBE DC ☐

19810 0170 FBR SPY 90 TUBE FBR ☐

19810 0170 FG SPY 90 TUBE FG ☐

19810 0170 GC SPY 90 TUBE GC ☐

19810 0170 PB SPY 90 TUBE PB ☐

19810 0170 W SPY 90 TUBE W ☐

Notes:

OBIN ON 92724 DIM8

30511 9228 W