





## SOLI - FORM 110 93067 MDL

27129 9320 W-W

AVAILABLE IN  
**BLACK-BLACK** 27129 9320 B-B  
**BLACK-FLEMISH GOLD** 27129 9320 B-FG  
**WHITE-BLACK** 27129 9320 W-B  
**WHITE-WHITE** 27129 9320 W-W



[View on website](#)



### General info

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                     |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted             |
| <b>INGRESS PROTECTION</b> | IP20                                                       |
| <b>WEIGHT (KG)</b>        | 0.9                                                        |
| <b>ADJUSTABILITY</b>      | non adjustable                                             |
| <b>INFORMATION</b>        | INCL.48 x REFLECTOR FL-67°<br>EXCL.LED POWER SUPPLY 48V-DC |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC, LCA                      |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3086lm |
| <b>TM-30 VALUES</b>                | Rf: 92 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG1                                                  |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>BEAMANGLE</b>                   | 67°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 3086lm // 22,3W // 138lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 2694lm // 25,6W // 105lm/W                           |

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27129\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### SMART 48

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

7

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

7

Dimtype: WDL = wireless dimmable


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

4

Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

9

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

4

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

8

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

| SOLISCAPE profile                                                                                                                     | Available Colours                 |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| <div><p><b>27111 0020</b> SOLI - PROFILE 2m</p></div> | <div><div></div><div></div></div> |
| <div><p><b>27111 0030</b> SOLI - PROFILE 3m</p></div> | <div><div></div><div></div></div> |

Notes: