



M20/M26H - OBIN 93036 DIM5

30514 9335 BRA

AVAILABLE IN

BLACK 30514 9335 B

BRUSHED ALU 30514 9335 BRA

BRUSHED ANTHRACITE 30514 9335 BRAT



BRUSHED BROWN BRONZE 30514 9335 BRBB

BRUSHED GOLD 30514 9335 BRG

BRUSHED OLD BRONZE 30514 9335 BROB

CREAM 30514 9335 CR

WHITE 30514 9335 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-36° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1315lm // 13,3W // 99lm/W

Requirements

SPY 90 TUBE
LED POWER SUPPLY 48V-DC

Accessories






HONEYCOMB 75

M20/M26H - OBIN 93036 DIM5

30514 9335 BRA

For detailed installation instructions, please consult the manual : [30514_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures	
		Min current Max current	
 55 100 90 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable			7
 63 114 125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable			14
 17 298 30 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40			7
 22 392 30 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40			14
Light altering devices			
 13 075 19810 0110 B HONEYCOMB 75 SINGLE USE B			

DELTALIGHT

M20/M26H - OBIN 93036 DIM5

30514 9335 BRA

Finish your product

	19810 0170 B	SPY 90 TUBE B	☐
	19810 0170 CR	SPY 90 TUBE CR	☐
	19810 0170 DC	SPY 90 TUBE DC	☐
	19810 0170 FBR	SPY 90 TUBE FBR	☐
	19810 0170 FG	SPY 90 TUBE FG	☐
	19810 0170 GC	SPY 90 TUBE GC	☐
	19810 0170 PB	SPY 90 TUBE PB	☐
	19810 0170 W	SPY 90 TUBE W	☐

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL


Available Colours

	30411 9205	SHIFTLINE M26H + SBL 2m DIM5	☒ ☐
	30411 9305	SHIFTLINE M26H + SBL 2m DIM5	☒ ☐
	30412 9205	SHIFTLINE M26H + SBL 3m DIM5	☒ ☐


DELTALIGHT

M20/M26H - OBIN 93036 DIM5


30514 9335 BRA



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5




SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m



DELTALIGHT

M20/M26H - OBIN 93036 DIM5

30514 9335 BRA




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: