



## OML50 - PRISMATIC LENS D HE 1312mm EM-3H 930

31225 9300 B

AVAILABLE IN  
**BLACK** 31225 9300 B

 [View on website](#)



### General info

|                           |  |
|---------------------------|--|
| <b>LOCATION</b>           | indoor                                     |
| <b>INGRESS PROTECTION</b> | IP20                                       |
| <b>WEIGHT (KG)</b>        | 1.9  |
| <b>INFORMATION</b>        | INCL.LED POWER SUPPLY<br>CABLING 1 CIRCUIT |

### Electrical info

|                     |                      |
|---------------------|----------------------|
| <b>ELECTRICAL</b>   | 220-240V / 0 50-60Hz |
| <b>CLASS</b>        | I                    |
| <b>POWER SUPPLY</b> | YES                  |
| <b>DIM TYPE</b>     | non-dimmable         |
| <b>ENERGY CLASS</b> | D                    |
| <b>CERTIFICATES</b> | EPD, RCM             |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED cluster 19,5W / CRI>90 (R9: 50) / 3000K / 3192lm |
| <b>TM-30 VALUES</b>                | Rf: 92 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L80 > 60000  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 3192lm // 19,5W // 164lm/W                           |

Notes: