
DELTALIGHT




M20/M26H - OBIN 93036 DIM5

REFERENCE 30514 9335 BRG

AVAILABLE IN
BLACK 30514 9335 B
BRUSHED ALU 30514 9335 BRA
BRUSHED ANTHRACITE 30514 9335 BRAT
BRUSHED BROWN BRONZE 30514 9335 BRBB
BRUSHED GOLD 30514 9335 BRG
BRUSHED OLD BRONZE 30514 9335 BROB
CREAM 30514 9335 CR
WHITE 30514 9335 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-36° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1315lm // 13,3W // 99lm/W

Requirements

SPY 90 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 75

DELTALIGHT

M20/M26H - OBIN 93036 DIM5

30514 9335 BRG

For detailed installation instructions, please consult the manual : **30514_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7 ☐

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 14 ☐


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 14 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices




19810 0110 B HONEYCOMB 75 SINGLE USE B ☐

DELTALIGHT


M20/M26H - OBIN 93036 DIM5

30514 9335 BRG

Finish your product

	**19810 0170 B** SPY 90 TUBE B	☐
	19810 0170 CR SPY 90 TUBE CR	☐
	19810 0170 DC SPY 90 TUBE DC	☐
	19810 0170 FBR SPY 90 TUBE FBR	☐
	19810 0170 FG SPY 90 TUBE FG	☐
	19810 0170 GC SPY 90 TUBE GC	☐
	19810 0170 PB SPY 90 TUBE PB	☐
	19810 0170 W SPY 90 TUBE W	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL	Available Colours
 **30411 9205** SHIFTLINE M26H + SBL 2m DIM5	● ○
 **30411 9305** SHIFTLINE M26H + SBL 2m DIM5	● ○
 **30412 9205** SHIFTLINE M26H + SBL 3m DIM5	● ○


DELTALIGHT

M20/M26H - OBIN 93036 DIM5


30514 9335 BRG



30412 9305 SHIFTLINE M26H + SBL 3m DIM5




30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5


SHIFTLINE M26H profile — Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m





DELTALIGHT

M20/M26H - OBIN 93036 DIM5

30514 9335 BRG



23397 0030 SPM20 ST - PROFILE 3m

SPLITLINE M20 profile	Available Colours
 **420 20 10 00** SPM20 - PROFILE 1m	
 **420 20 20 00** SPM20 - PROFILE 2m	
 **420 20 30 00** SPM20 - PROFILE 3m	
 **23301 0000** SPM20 - PROFILE B	

Notes: