



M26L - SPY 391 93020 DIM5

23259 9325 PB

AVAILABLE IN

SCHWARZ 23259 9325 B

ALU GEBÜSTET 23259 9325 BRA

GEBÜSTETES ANTHRAZIT 23259 9325 BRAT

GEBÜSTETES KUPFER 23259 9325 BRCU

GEBÜSTETES GOLD 23259 9325 BRG

GEBÜSTETE ALTE BRONZE 23259 9325 BROB



FLEMISH BRONZE 23259 9325 FBR

FLEMISH GOLD 23259 9325 FG

GOLDFARBEN 23259 9325 GC

KLAVIER SCHWARZ 23259 9325 PB

WEISS 23259 9325 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Niederspannungssysteme Niederspannungssysteme montiert
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° schwenkbar, 360° drehbar
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	888lm // 9,9W // 90lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie






Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23259_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED Betriebsgeräte		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: nicht dimmbar	10	
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: nicht dimmbar	24	
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: nicht dimmbar Cutout dimension (mm): 40	10	
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: nicht dimmbar Cutout dimension (mm): 40	20	
 24144 0030 B VISOR 39 B		

M26L - SPY 391 93020 DIM5

Beenden Sie Ihr Produkt

☐☐☐☐





Available Colours



DELTALIGHT

M26L - SPY 391 93020 DIM5

23259 9325 PB

SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	
	23375 0030 SLM35R - PROFILE 3m	

Notes: