




OML50 - INFORM D HE 2624mm 8+16+8LED 94063 DIM5

31423 9435 B

BESCHIKBAAR IN
ZWART 31423 9435 B



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0
INFO	CLUSTER DOWN: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm
TM-30-15 WAARDEN	Rf: 90 / Rg: 101
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	5286lm // 32,6W // 162lm/W

Opties	
WIRELESS CONTROL DIM5	

Notes: