



MINIGRID ON 350 93033 DIM8

100046 9328 B-W



AVAILABLE IN

BLACK-BLACK 100046 9328 B-B

BLACK-WHITE 100046 9328 B-W

WHITE-BLACK 100046 9328 W-B

WHITE-WHITE 100046 9328 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.6
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	3 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	3267lm // 25,8W // 127lm/W
LED TECHNICS (LUMINAIRE)	2660lm // 29,7W // 90lm/W

For detailed installation instructions, please consult the manual : [100046_XXX8_HAND.pdf](#)

MINIGRID ON 350 93033 DIM8

100046 9328 B-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: