



M52 - SPY 52 92730 DIM5

24435 9245 FG

AVAILABLE IN



BLACK 24435 9245 B

FLEMISH BRONZE 24435 9245 FBR

FLEMISH GOLD 24435 9245 FG

GOLD COLOURED 24435 9245 GC

WHITE 24435 9245 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC Optional REFLECTORS 20° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 60) / 2700K / 1403lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	895lm // 14,3W // 63lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42

SPREAD LENS 42







LINEAR SPREAD LENS 42

SOFTENING LENS 42

GLASS SBL 42

For detailed installation instructions, please consult the manual : [24435_XXX5_HAND.pdf](#)



FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures	
		Min current Max current	
 55 100 90 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable			7
 63 114 125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable			16
 17 298 30 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40			7
 22 392 30 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40			14
Light altering devices			
 13 Ø42 19810 0010 B HONEYCOMB 42 SINGLE USE B			
 13 Ø42 19810 0020 LINEAR SPREAD LENS 42			


DELTALIGHT

M52 - SPY 52 92730 DIM5

24435 9245 FG

	19810 0030	SPREAD LENS 42	☐
	19810 0040	SOFTENING LENS 42	☐
	19810 0050	GLASS SBL 42	☐
	19810 0060 B	HONEYCOMB 42 DOUBLE USE B	☐

Finish your product

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	19810 0180	SPY 52 REFLECTOR 20°	☐
--	-------------------	----------------------	--------------------------

DELTALIGHT

M52 - SPY 52 92730 DIM5

24435 9245 FG







19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°



COMPATIBLE COMPOSABLES

SPLITLINE M52 profile	Available Colours
 420 52 10 00 SPM52 - PROFILE 1m	
 420 52 20 00 SPM52 - PROFILE 2m	
 420 52 30 00 SPM52 - PROFILE 3m	
 24413 0000 SPM52 - PROFILE	

Notes: