
DELTALIGHT




# SUPERLOOP-SPY 52 92730 MDL

**REFERENCE** 20567 9240 W

AVAILABLE IN
**BLACK** 20567 9240 B
**FLEMISH BRONZE** 20567 9240 FBR
**FLEMISH GOLD** 20567 9240 FG
**GOLD COLOURED** 20567 9240 GC
**WHITE** 20567 9240 W



View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-30°<br>INCL.CLIP 48V ADAPTER<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 20° & 45° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 30° |
| **LED TECHNICS (LIGHT SOURCE)** | 1041lm // 8,6W // 121lm/W |
| **LED TECHNICS (LUMINAIRE)** | 664lm // 9,9W // 67lm/W |

**Requirements**

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

**Options**

DIMMABLE MODULATOR

**Accessories**

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42

DELTALIGHT

# SUPERLOOP-SPY 52 92730 MDL

20567 9240 W

GLASS SBL 42

For detailed installation instructions, please consult the manual : **20567_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### SMART 48

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 19

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 19


**Dimtype: WDL = wireless dimmable**

### LED power supplies

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 10

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 24

**Dimtype: non-dimmable**





**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 10

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

# SUPERLOOP-SPY 52 92730 MDL

20567 9240 W





**21012 0240** LED POWER SUPPLY 48V-DC / 200W 20


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**


## Light altering devices





**19810 0010 B** HONEYCOMB 42 SINGLE USE B





**19810 0020** LINEAR SPREAD LENS 42





**19810 0030** SPREAD LENS 42




**19810 0040** SOFTENING LENS 42





**19810 0050** GLASS SBL 42




**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

## Finish your product




**19810 0100 B** SPY 52 TUBE B


**19810 0100 FBR** SPY 52 TUBE FBR

## SUPERLOOP-SPY 52 92730 MDL


20567 9240 W

| | |
|---|---|
| **19810 0100 FG** | SPY 52 TUBE FG |
| **19810 0100 GC** | SPY 52 TUBE GC |
| **19810 0100 W** | SPY 52 TUBE W |


### Replaceable reflector / lens




**19810 0180** SPY 52 REFLECTOR 20°





**19810 0190** SPY 52 REFLECTOR 45°





**19810 0240** SPY 52 REFLECTOR 30°

## COMPATIBLE COMPOSABLES


### SUPERLOOP HC MDL — Available Colours




**418 481 07** SUPERLOOP HC 70 MDL




**418 481 09** SUPERLOOP HC 90 MDL





**418 481 12** SUPERLOOP HC 120 MDL

DELTALIGHT

# SUPERLOOP-SPY 52 92730 MDL


20567 9240 W





**418 481 17** SUPERLOOP HC 170 MDL

## SUPERLOOP HC MDL XL


Available Colours





**20555 0000** SUPERLOOP HC 200 MDL





**20556 0000** SUPERLOOP HC 250 MDL





**20557 0000** SUPERLOOP HC 300 MDL




**20558 0000** SUPERLOOP HC 350 MDL





**20559 0000** SUPERLOOP HC 400 MDL





**20560 0000** SUPERLOOP HC 500 MDL

## SUPERLOOP PLUS MDL

Available Colours




**20564 0000** SUPERLOOP PLUS HC 70 MDL





**20565 0000** SUPERLOOP PLUS HC 90 MDL





DELTALIGHT

# SUPERLOOP-SPY 52 92730 MDL

20567 9240 W




**20566 0000** SUPERLOOP PLUS HC 120 MDL

| SUPERLOOP S HC MDL | Available Colours |
|---|---|
|  **418 482 106** SUPERLOOP S HC 106 MDL | |
|  **418 482 109** SUPERLOOP S HC 109 MDL | |
|  **418 482 211** SUPERLOOP S HC 211 MDL | |
|  **418 482 217** SUPERLOOP S HC 217 MDL | |









Notes: