

## INFORM SQ P282-10 DOWN 92767

25521 9220 W-B



AVAILABLE IN

**BLACK-BLACK** 25521 9220 B-B

**BLACK-FLEMISH GOLD** 25521 9220 B-FG

**WHITE-BLACK** 25521 9220 W-B

**WHITE-WHITE** 25521 9220 W-W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.9
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	120 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 1000/1500mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 35,2-55,8W / CRI>90 (R9: 50) / 2700K / 5064-7320lm
<b>TM-30 VALUES</b>	Rf: 93 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	67°
<b>LED TECHNICS (LIGHT SOURCE)</b>	7320lm // 55,8W // 131lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	6390lm // 64,2W // 100lm/W

### Requirements

INFORM SQ POWERBOX 75W (DIM5)

INFORM POWER SUPPLY 60W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : [25521\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## INFORM SQ P282-10 DOWN 92767

25521 9220 W-B

### FINISH YOUR SPECIFICATION


#### Power box

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**25510 0020 B** INFORM SQ POWERBOX 75W B

1

Dimtype: non-dimmable

**25510 0020 W** INFORM SQ POWERBOX 75W W

1



**25510 0025 B** INFORM SQ POWERBOX 75W DIM5 B

1

Dimtype: DALI

**25510 0025 W** INFORM SQ POWERBOX 75W DIM5 W

1


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**25510 0405** INFORM POWER SUPPLY 60W DIM5

1

Dimtype: DALI



**25510 0450** INFORM POWER SUPPLY 60W

1

Dimtype: non-dimmable

#### Electric connection parts

#### # of Fixtures




# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

# DELTALIGHT

## INFORM SQ P282-10 DOWN 92767

25521 9220 W-B



**15225 0350 B** SUSPENSION + CONNECTION ST B

2 needed

**Cutout dimension (mm): 27**

**15225 0350 W** SUSPENSION + CONNECTION ST W

2 needed

Notes: