





INFORM 40 SQ 180 DOWN-UP 94063 DIM5

30723 9435 B-B

AVAILABLE IN

BLACK-BLACK 30723 9435 B-B

WHITE-BLACK 30723 9435 W-B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm UP (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm Or DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101 DOWN: rf: 90 / Rg: 101 UP: rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 3642lm // 24,2W // 151lm/W UP (HO): 3642lm // 24,2W // 151lm/W Or DOWN: 2643lm // 16,3W // 162lm/W UP: 2643lm // 16,3W // 162lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 2520lm // 27,8W // 91lm/W UP (HO): 2398lm // 27,8W // 86lm/W Or DOWN: 1829lm // 18,7W // 98lm/W UP: 1741lm // 18,7W // 93lm/W

Options

CABLE BASE R / S

DELTA LIGHT


INFORM 40 SQ 180 DOWN-UP 94063 DIM5

30723 9435 B-B

For detailed installation instructions, please consult the manual : [30723_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Notes: