

MINI DEEP RINGO II 93037

19423 9330 BRCU

AVAILABLE IN

BLACK 19423 9330 B

BRUSHED ALU 19423 9330 BRA

BRUSHED ANTHRACITE 19423 9330 BRAT

BRUSHED BROWN BRONZE 19423 9330 BRBB

BRUSHED COPPER 19423 9330 BRCU

BRUSHED GOLD 19423 9330 BRG


BRUSHED OLD BRONZE 19423 9330 BROB

CREAM 19423 9330 CR

FLEMISH BRONZE 19423 9330 FBR

FLEMISH GOLD 19423 9330 FG

WHITE 19423 9330 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 56
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-37° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	37°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	678lm // 9,9W // 69lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

DELTALIGHT

MINI DEEP RINGO II 93037

19423 9330 BRCU

For detailed installation instructions, please consult the manual : [19423_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

Dimtype: 1-10V

Cutout dimension (mm): 30

2

DELTALIGHT

MINI DEEP RINGO II 93037

19423 9330 BRCU



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72

DELTALIGHT

MINI DEEP RINGO II 93037

19423 9330 BRCU



300 90 67

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2 | -



Dimtype: 1-10V or DALI or push button



300 90 68

LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 72



300 90 69

LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 124

LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125

LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 55



300 90 135

LED POWER SUPPLY MULTI-POWER HV

3->4 | 2->4



Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010

LED POWER SUPPLY MULTI POWER

2 | 2



Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021

LED POWER SUPPLY MULTI POWER DIM1

3 | 3



Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035

LED POWER SUPPLY MULTI POWER DIM5

3 | 3



Dimtype: DALI

Cutout dimension (mm): 54



21012 004W

LED POWER SUPPLY MULTI-POWER WDL

4(4) | 4(3)



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84

DELTALIGHT

MINI DEEP RINGO II 93037

19423 9330 BRCU



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60

DELTALIGHT

MINI DEEP RINGO II 93037

19423 9330 BRCU



21032 0295

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 30



21032 0305

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 30

Notes: