



## SOLI - FORM 60 92767 DIM5

27130 9225 W-W

AVAILABLE IN

**BLACK-BLACK** 27130 9225 B-B

**BLACK-FLEMISH GOLD** 27130 9225 B-FG

**WHITE-BLACK** 27130 9225 W-B

**WHITE-WHITE** 27130 9225 W-W



[View on website](#)



### General info

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                     |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted             |
| <b>INGRESS PROTECTION</b> | IP20                                                       |
| <b>WEIGHT (KG)</b>        | 0.5                                                        |
| <b>ADJUSTABILITY</b>      | non adjustable                                             |
| <b>INFORMATION</b>        | INCL.24 x REFLECTOR FL-67°<br>EXCL.LED POWER SUPPLY 48V-DC |

### Electrical info

|                     |               |
|---------------------|---------------|
| <b>ELECTRICAL</b>   | 48V-DC        |
| <b>CLASS</b>        | III           |
| <b>DIM TYPE</b>     | DALI          |
| <b>ENERGY CLASS</b> | E             |
| <b>CERTIFICATES</b> | CB, ENEC, LCA |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 11,2W / CRI>90 (R9: 50) / 2700K / 1464lm |
| <b>TM-30 VALUES</b>                | Rf: 93 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG1                                                  |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>BEAMANGLE</b>                   | 67°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1464lm // 11,2W // 131lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1278lm // 12,9W // 99lm/W                            |

### Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27130\\_XXX5\\_HAND.pdf](#)

SOLI - FORM 60 92767 DIM5

27130 9225 W-W

FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                          |    | # of Fixtures             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------|
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |    | Min current   Max current |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>5510090</div></div></div> <div><div><div>300 89 48 100</div><div>LED POWER SUPPLY 48V-DC / 100W DIN</div></div><div>Dimtype: non-dimmable</div></div>                                                                                                           | 8  | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>63114125</div></div></div> <div><div><div>300 89 48 240</div><div>LED POWER SUPPLY 48V-DC / 240W DIN</div></div><div>Dimtype: non-dimmable</div></div>                                                                                                          | 20 | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>1729830</div></div></div> <div><div><div>21012 0230</div><div>LED POWER SUPPLY 48V-DC / 100W</div></div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div>                                                                              | 8  | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>2239230</div></div></div> <div><div><div>21012 0240</div><div>LED POWER SUPPLY 48V-DC / 200W</div></div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div>                                                                              | 17 | <div></div>               |

COMPATIBLE COMPOSABLES

| SOLISCAPE profile                                                                                                                                                                          | Available Colours                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>2319</div></div></div> <div><div><div>27111 0020</div><div>SOLI - PROFILE 2m</div></div></div> | <div><div></div><div></div></div> |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>2319</div></div></div> <div><div><div>27111 0030</div><div>SOLI - PROFILE 3m</div></div></div> | <div><div></div><div></div></div> |

Notes:

# DELTALIGHT

## **SOLI - FORM 60 92767 DIM5**

27130 9225 W-W