



MONTUR S P 65 LED 930

232 472 93 N

AVAILABLE IN
BLACK 232 472 93 B
ANTHRACITE 232 472 93 N



[View on website](#)




General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	5.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC
Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6,3W / CRI>90 (R9: 50) / 3000K / 925lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	925lm // 6,3W // 147lm/W
LED TECHNICS (LUMINAIRE)	555lm // 7,2W // 77lm/W

- Options**
- PLATE 3
 - CBOX
 - IP68 CONNECTION KIT
 - IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [232_472_XX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 02 03 PLATE 3

☐

Notes: