



SL19 - SPY 39 FOCUS 930 DIM5

27037 9305 FG

AVAILABLE IN
BLACK 27037 9305 B
FLEMISH BRONZE 27037 9305 FBR
FLEMISH GOLD 27037 9305 FG
GOLD COLOURED 27037 9305 GC
WHITE 27037 9305 W



 [View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.3 |
| ADJUSTABILITY | 0° to 85° swiveling, 355° rotatable |
| INFORMATION | ADJUSTABLE BEAM 15°-45° |

Electrical info

| | |
|---------------------|----------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | DALI |
| ENERGY CLASS | E |
| CERTIFICATES | CB, ENEC |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm |
| TM-30 VALUES | rf: 90 / Rg: 99 |
| SDCM | SDCM1 |
| RISKGROUPE | RG1 |
| LM80 | L90B10 > 50000 |
| BEAMANGLE | 15°-45° |
| LED TECHNICS (LIGHT SOURCE) | 1018lm // 8,6W // 118lm/W |
| LED TECHNICS (LUMINAIRE) | 303lm // 9,9W // 31lm/W |

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27037_XXX5_HAND.pdf](#)

DELTALIGHT

SL19 - SPY 39 FOCUS 930 DIM5

27037 9305 FG

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20


Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile

Available Colours



27011 0060 SL19 - PROFILE 3m



Notes: