DELTALIGHT



COMPO S HP TW 94020

REFERENCE 9 15722 9020 C

AVAILABLE IN
BLACK 9 15722 9020 B
CHROMED 9 15722 9020 C
DARK CHROMED 9 15722 9020 DC
WHITE 9 15722 9020 W



View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.18
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 7W / CRI>90 / 1800K-4000K / 605lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	605lm // 7W // 89lm/W
LED TECHNICS (LUMINAIRE)	363lm // 9W // 43lm/W

Requirements

LED POWER SUPPLY 200 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B
COMPO S LINEAR SPREAD LENS
COMPO S SPREAD LENS
COMPO S SOFTENING LENS
COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : **9_15722_XXX0_HAND.pdf**

DELTALIGHT

COMPO S HP TW 94020

9 15722 9020 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Plasterboard**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Wood**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 5800	LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA	1

Notes: