





SUPERNOVA LINE 125 DOWN-UP 930 DIM5

20620 9305 B

AVAILABLE IN
BLACK 20620 9305 B
WHITE 20620 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	21
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY CABLING 2 CIRCUITS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 3 x 0.75mm ² + 1 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 235,2W / CRI>90 (R9: 50) / 3000K / 3454lm UP: 6 x (LED cluster 7,4W / CRI>90 (R9: 50) / 3000K / 1079lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3454lm // 235,2W // 147lm/W UP: 6474lm // 44,4W // 147lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 26534lm // 270,5W // 98lm/W UP: 5988lm // 51,1W // 117lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS
WIRELESS CONTROL DIM5

DELTALIGHT


SUPERNOVA LINE 125 DOWN-UP 930 DIM5

20620 9305 B


For detailed installation instructions, please consult the manual : [20620_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Miscellaneous control equipment

	300 90 004 ED5 WIRELESS CONTROL DIM5	☐
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 45	






Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐

DELTALIGHT

SUPERNOVA LINE 125 DOWN-UP 930 DIM5

20620 9305 B

	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐

DELTA LIGHT

SUPERNOVA LINE 125 DOWN-UP 930 DIM5


20620 9305 B

204 90 90 W

COVERSET S 90 W



Suspension parts



328 10 01

SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B

SUSPENSION ST B

☐


Cutout dimension (mm): 27

15225 0340 W

SUSPENSION ST W



Electric connection parts



328 10 03

CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B

CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W

CONNECTION ST W



Notes: