
DELTALIGHT




SUPERNOVA LINE 125 DOWN-UP 930 DIM5

REFERENCE 20620 9305 B

AVAILABLE IN
NEGRO 20620 9305 B
BLANCO 20620 9305 W





View on website

General info	
LOCATION	interior
INSTALLATION	Techo Suspendido
INGRESS PROTECTION	IP20
WEIGHT (KG)	21
ADJUSTABILITY	no ajustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY CABLING 2 CIRCUITS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 3 x 0.75mm² + 1 x CABLE 2 x 0.75mm²

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	con DALI
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 235,2W / CRI>90 (R9: 50) / 3000K / 34541lm UP: 6 x (LED cluster 7,4W / CRI>90 (R9: 50) / 3000K / 1079lm)
RVALUES	Rf: 92 / Rg: 100
SDMC	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 34541lm // 235,2W // 147lm/W UP: 6474lm // 44,4W // 147lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 26534lm // 270,5W // 98lm/W UP: 5988lm // 51,1W // 117lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS
WIRELESS CONTROL DIM5

DELTALIGHT


SUPERNOVA LINE 125 DOWN-UP 930 DIM5

20620 9305 B

For detailed installation instructions, please consult the manual : **20620_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION


Cable de alimentación



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐




203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Equipos de control diversos




300 90 004 ED5 WIRELESS CONTROL DIM5 ☐

Dimtype: WDL = Regulable inalámbrico

Cutout dimension (mm): 45

Plafones








204 00 62 ANO COVERSET R 62 ANO ☐

204 00 62 B COVERSET R 62 B ☐

DELTALIGHT

SUPERNOVA LINE 125 DOWN-UP 930 DIM5

20620 9305 B


	204 00 62 W	COVERSET R 62 W	☐
	**204 00 90 ANO**	COVERSET R 90 ANO	☐
	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐

SUPERNOVA LINE 125 DOWN-UP 930 DIM5

20620 9305 B


204 90 90 W COVERSET S 90 W

Accesorios de Suspensión



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Partes para conexión eléctrica



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: