





M20/M26H - SPY 66 93018 MDL

23327 9310 W

AVAILABLE IN  
**BLACK** 23327 9310 B  
**WHITE** 23327 9310 W



 [View on website](#)



| General info       |                                                                                             |
|--------------------|---------------------------------------------------------------------------------------------|
| LOCATION           | indoor                                                                                      |
| INSTALLATION       | Low voltage systems Low voltage system mounted                                              |
| INGRESS PROTECTION | IP20                                                                                        |
| WEIGHT (KG)        | 0.6                                                                                         |
| ADJUSTABILITY      | 0° to 90° swiveling, 355° rotatable                                                         |
| INFORMATION        | REFLECTOR SP-18°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

| Electrical info |                                    |
|-----------------|------------------------------------|
| ELECTRICAL      | 48V-DC                             |
| CLASS           | III                                |
| DIM TYPE        | MDL = 1-10V or DALI or push button |
| ENERGY CLASS    | E                                  |
| CERTIFICATES    | CB, ENEC, EPD                      |

| Lightsource info            |                                                  |
|-----------------------------|--------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                              |
| LIGHTSOURCE                 | LED array 25W / CRI>90 (R9: 52) / 3000K / 2811lm |
| TM-30 VALUES                | rf: 90 / Rg: 99                                  |
| SDCM                        | SDCM1                                            |
| RISKGROUP                   | RG1                                              |
| LM80                        | L90B10 > 50000                                   |
| BEAMANGLE                   | 18°                                              |
| LED TECHNICS (LIGHT SOURCE) | 2811lm // 25W // 112lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 2007lm // 28,8W // 70lm/W                        |

| Remarks                                                    |
|------------------------------------------------------------|
| Take a look at our <a href="#">MAGNETIC PROFILES</a> movie |

| Requirements                           |
|----------------------------------------|
| SPY 66 TUBE<br>LED POWER SUPPLY 48V-DC |

| Options            |
|--------------------|
| DIMMABLE MODULATOR |

| Accessories  |
|--------------|
| HONEYCOMB 57 |

For detailed installation instructions, please consult the manual : [23327\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

**Current supply**

**# of Fixtures**

**Min current | Max current**

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



**21032 0030** SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = wireless dimmable

6

**SMART 48**

**# of Fixtures**

**Min current | Max current**


 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



**300 90 011** SMART 48 MODULATOR DIM9

Dimtype: 1-10V or DALI or push button

6



**300 90 012** SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable


6

**LED power supplies**

**# of Fixtures**

**Min current | Max current**

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

Dimtype: non-dimmable

3

# DELTALIGHT

## M20/M26H - SPY 66 93018 MDL


23327 9310 W

|                                                                                  |                                                         |   |                          |
|----------------------------------------------------------------------------------|---------------------------------------------------------|---|--------------------------|
|  | <b>300 89 48 240</b> LED POWER SUPPLY 48V-DC / 240W DIN | 8 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |   |                          |
|  | <b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W        | 3 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |   |                          |
| Cutout dimension (mm): 40                                                        |                                                         |   |                          |
|  | <b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W        | 7 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |   |                          |
| Cutout dimension (mm): 40                                                        |                                                         |   |                          |

### Light altering devices

|                                                                                    |                                               |                          |
|------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------|
|  | <b>24611 0150 B</b> HONEYCOMB 57 SINGLE USE B | <input type="checkbox"/> |
|------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------|

### Finish your product

|                                                                                    |                                       |                          |
|------------------------------------------------------------------------------------|---------------------------------------|--------------------------|
|  | <b>24611 0100 B</b> SPY 66 TUBE B     | <input type="checkbox"/> |
|                                                                                    | <b>24611 0100 FBR</b> SPY 66 TUBE FBR | <input type="checkbox"/> |
|                                                                                    | <b>24611 0100 FG</b> SPY 66 TUBE FG   | <input type="checkbox"/> |
|                                                                                    | <b>24611 0100 GC</b> SPY 66 TUBE GC   | <input type="checkbox"/> |
|                                                                                    | <b>24611 0100 W</b> SPY 66 TUBE W     | <input type="checkbox"/> |

# DELTALIGHT

## M20/M26H - SPY 66 93018 MDL

23327 9310 W

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°



**24611 0230** SPY 66 REFLECTOR 30°




**24611 0240** SPY 66 REFLECTOR 45°




### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26H profile


#### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



#### SPLITLINE M20 ST profile

#### Available Colours



**23397 0000** SPM20 ST - PROFILE



# DELTALIGHT

## M20/M26H - SPY 66 93018 MDL

23327 9310 W



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: