
DELTALIGHT




INFORM SQ P200-7 DOWN-UP 94067

REFERENCE 25518 9420 B-B

AVAILABLE IN
BLACK-BLACK 25518 9420 B-B
BLACK-FLEMISH GOLD 25518 9420 B-FG
WHITE-BLACK 25518 9420 W-B
WHITE-WHITE 25518 9420 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	84 x REFLECTOR FL-67° (DOWN) EXCL.LED POWER SUPPLY 1300mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 24,6W / CRI>90 (R9: 50) / 4000K / 3898lm UP: LED cluster 21,1W / CRI>90 (R9: 50) / 4000K / 3341lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3898lm // 24,6W // 158lm/W UP: 3341lm // 21,1W // 158lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 3306lm // 28,3W // 117lm/W UP: 2252lm // 24,3W // 93lm/W

Requirements

INFORM SQ POWERBOX 75W (DIM5)
INFORM POWER SUPPLY 60W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : **25518_XXX0_HAND.pdf**

DELTALIGHT

INFORM SQ P200-7 DOWN-UP 94067

25518 9420 B-B


FINISH YOUR SPECIFICATION

Power box

# of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



25510 0020 B INFORM SQ POWERBOX 75W B — 1

Dimtype: non-dimmable

25510 0020 W INFORM SQ POWERBOX 75W W — 1



25510 0025 B INFORM SQ POWERBOX 75W DIM5 B — 1

Dimtype: DALI


25510 0025 W INFORM SQ POWERBOX 75W DIM5 W — 1

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



25510 0405 INFORM POWER SUPPLY 60W DIM5 — 1

Dimtype: DALI



25510 0450 INFORM POWER SUPPLY 60W — 1

Dimtype: non-dimmable

Electric connection parts

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

DELTALIGHT

INFORM SQ P200-7 DOWN-UP 94067

25518 9420 B-B



15225 0350 B SUSPENSION + CONNECTION ST B — 2 needed

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W — 2 needed

Notes: