



MULTINOVA 55 DOWN-UP TW 930 DIM5



28020 9005 W

AVAILABLE IN

BLACK 28020 9005 B

GOLD COLOURED 28020 9005 GC

WHITE 28020 9005 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY - DALI (DT8)

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 29,1W / CRI>90 (R9: 63) / 2700K-6500K / 4191lm UP @ 2700K: LED cluster 4,3W / CRI>90 (R9: 63) / 2700K-6500K / 621lm Or DOWN @ 6500K: LED cluster 29,2W / CRI>90 (R9: 81) / 2700K-6500K / 4465lm UP @ 6500K: LED cluster 4,3W / CRI>90 (R9: 81) / 2700K-6500K / 661lm
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 4191lm // 29,1W // 144lm/W UP @ 2700K: 621lm // 4,3W // 144lm/W Or DOWN @ 6500K: 4465lm // 29,2W // 153lm/W UP @ 6500K: 661lm // 4,3W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 3378lm // 33,5W // 101lm/W UP @ 2700K: 588lm // 4,9W // 119lm/W Or DOWN @ 6500K: 3598lm // 33,6W // 107lm/W UP @ 6500K: 626lm // 4,9W // 127lm/W

Options

MULTINOVA 55 SUSPENSION SET
MULTINOVA ROD SUSPENSION

DELTALIGHT




MULTINOVA 55 DOWN-UP TW 930 DIM5

28020 9005 W

For detailed installation instructions, please consult the manual : [28020_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Suspension parts

	27910 0010 B MULTINOVA 55 SUSPENSION SET 5x0,75 3m B	☐
	27910 0010 W MULTINOVA 55 SUSPENSION SET 5x0,75 3m W	☐
	27910 0030 B MULTINOVA 55 ROD SUSPENSION 0,4m B	☐
	27910 0030 W MULTINOVA 55 ROD SUSPENSION 0,4m W	☐
	27910 0040 B MULTINOVA 55 ROD SUSPENSION 0,8m B	☐
	27910 0040 W MULTINOVA 55 ROD SUSPENSION 0,8m W	☐

Notes: