



## COMPO S HP TW 94020

9 15722 9020 B


AVAILABLE IN

**BLACK** 9 15722 9020 B

**CHROMED** 9 15722 9020 C

**DARK CHROMED** 9 15722 9020 DC

**WHITE** 9 15722 9020 W



[View on website](#)



| General info                       |                                     |
|------------------------------------|-------------------------------------|
| LOCATION                           | indoor                              |
| INSTALLATION                       | Ceiling Recessed                    |
| CUTOUT SHAPE/SIZE (MM)             | round - 120                         |
| RECESSED DEPTH (MM)                | 114                                 |
| THICKNESS OF MOUNTING SURFACE (MM) | max.25                              |
| INGRESS PROTECTION                 | IP20                                |
| WEIGHT (KG)                        | 0.18                                |
| ADJUSTABILITY                      | 0° to 30° swiveling, 355° rotatable |

| Electrical info |                           |
|-----------------|---------------------------|
| CLASS           | III                       |
| DIM TYPE        | depending on power supply |
| ENERGY CLASS    | D                         |

| Lightsource info            |                                             |
|-----------------------------|---------------------------------------------|
| LIGHTSOURCE NAME            | LED                                         |
| LIGHTSOURCE                 | LED array 7W / CRI>90 / 1800K-4000K / 605lm |
| TM-30 VALUES                | rf: 89 / Rg: 100                            |
| SDCM                        | SDCM2                                       |
| RISKGROUP                   | RG1                                         |
| LM80                        | L90B10 > 56000                              |
| BEAMANGLE                   | 20°                                         |
| LED TECHNICS (LIGHT SOURCE) | 605lm // 7W // 89lm/W                       |
| LED TECHNICS (LUMINAIRE)    | 363lm // 8,5W // 43lm/W                     |

### Requirements

LED POWER SUPPLY 200 mA - DC

### Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9\\_15722\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

| Ceiling Type                                                                     | Mounting Kit                                                                                                                 |          |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------|
|  |  15710 0010 - MOUNTING KIT COMPO S TRIM     | Required |
|                                                                                  |  15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |
|  |  15710 0010 - MOUNTING KIT COMPO S TRIM     | Required |
|                                                                                  |  15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |
|  |  15710 0010 - MOUNTING KIT COMPO S TRIM     | Required |
|                                                                                  |  15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |

### FINISH YOUR SPECIFICATION

#### LED Power supply

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

**15710 5800** LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA

1

Notes: