




M26L - HEDRA L 93033 MDL

REFERENCE 23252 9320 BBR

AVAILABLE IN
BLACK BRONZE 23252 9320 BBR
GOLD COLOURED 23252 9320 GC



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	547lm // 9,9W // 55lm/W

Remarks
Take a look at our MAGNETIC PROFILES movie

Requirements
VIZIR TUBE LED POWER SUPPLY 48V-DC

Options
DIMMABLE MODULATOR

Accessories
VIZIR HONEYCOMB VIZIR SOFTENING LENS

For detailed installation instructions, please consult the manual : [23252_XXXX_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

16


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

16


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

8






Dimtype: non-dimmable

Cutout dimension (mm): 75

DELTALIGHT

M26L - HEDRA L 93033 MDL

23252 9320 BBR



	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	8	☐
Dimtype: non-dimmable			
	300 89 48 150 LED POWER SUPPLY 48V-DC / 150W	12	☐
Dimtype: non-dimmable			
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	16	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			

Power box

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '!' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current


	23377 0010 B SLM26L - POWERBOX 48V-DC / 96W B	8	☐
Dimtype: non-dimmable			
	23377 0010 W SLM26L - POWERBOX 48V-DC / 96W W	8	☐
	23377 0020 B SLM26L - MID POWERBOX 48V-DC / 96W B	8	☐
Dimtype: non-dimmable			
	23377 0020 W SLM26L - MID POWERBOX 48V-DC / 96W W	8	☐

DELTALIGHT


M26L - HEDRA L 93033 MDL

23252 9320 BBR

Light altering devices




473 03 01 B VIZIR HONEYCOMB B

☐

473 03 04 VIZIR SOFTENING LENS

☐

Finish your product



473 01 00 B VIZIR TUBE B

☐

473 01 00 FBR VIZIR TUBE FBR

☐

473 01 00 FG VIZIR TUBE FG

☐


473 01 00 W VIZIR TUBE W

☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m




23358 0020 SLM26L - PROFILE 2m



DELTALIGHT

M26L - HEDRA L 93033 MDL

23252 9320 BBR




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours




23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m



Notes: