



OML50 - PRISMATIC LENS D TW 1312mm EM-3H 950 DIM5

31226 9005 B

AVAILABLE IN
BLACK 31226 9005 B

 [View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 24W / CRI>90 (R9: 50) / 2700K-5000K / 3209lm Or @ 5000K: LED cluster 22W / CRI>90 (R9: 50) / 2700K-5000K / 3825lm
SDCM	SDCM3
RISKGROUP	RG1
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 3209lm // 24W // 134lm/W Or @ 5000K: 3825lm // 22W // 174lm/W

Options

WIRELESS CONTROL DIM5

Notes: