





## SL19 - SPY 39 FOCUS 930 DIM5

27037 9305 W

AVAILABLE IN  
**BLACK** 27037 9305 B  
**FLEMISH BRONZE** 27037 9305 FBR  
**FLEMISH GOLD** 27037 9305 FG  
**GOLD COLOURED** 27037 9305 GC  
**WHITE** 27037 9305 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 355° rotatable
<b>INFORMATION</b>	ADJUSTABLE BEAM 15°-45°

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUPE</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	15°-45°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1018lm // 8,6W // 118lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	303lm // 9,9W // 31lm/W

### Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27037\\_XXX5\\_HAND.pdf](#)

# DELTALIGHT

## SL19 - SPY 39 FOCUS 930 DIM5

27037 9305 W

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20


Dimtype: non-dimmable

Cutout dimension (mm): 40

### COMPATIBLE COMPOSABLES

#### SHIFTLINE 19 profile

#### Available Colours



**27011 0060** SL19 - PROFILE 3m



Notes: