


27037 9305 W

Fig. 10 is a detailed view of the connection between the cable (160) and the cable support (11). The cable support (11) is shown as a cylindrical component with a diameter of Ø39. The cable (160) is shown as a long, thin component with a diameter of 160. The connection is secured by a nut (17) and a washer (92).



Bekijk op website

LED POWER SUPPLY 48V-DC

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026

VERVOLLEDIG UW SPECIFICATIE


LED voedingen

armaturen



armaturen geeft aan hoeveel toestellen op de voeding kunnen worden aangesloten (min -> max). De waarden vóór en na de 'l' komen respectievelijk overeen met de minimale en maximale aanstroom. Waarden tussen haakjes zijn van toepassing op 110V.


Min. stroom | Max. stroom



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: niet dimbaar



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: niet dimbaar




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: niet dimbaar

Uitsparingsmaat (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20


Dimtype: niet dimbaar

Uitsparingsmaat (mm): 40

COMPATIBELE DRAAGSTRUCTUREN

SHIFTLINE 19 profile

Beschikbare kleuren



27011 0060 SL19 - PROFILE 3m



Notes: