DELTALIGHT

MINIGRID IN TRIMLESS 2 HI LED

PRODUCTREFERENTIE 100015 0000 W-W

BESCHIKBAAR IN
ZWART-ZWART 100015 0000 B-B
ZWART-WIT 100015 0000 B-W
WIT-ZWART 100015 0000 W-B
WIT-WIT 100015 0000 W-W





Bekijk op website

Algemene info	
LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rechthoekig - KIT
INBOUWDIEPTE (MM)	85
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.9
RICHTBAARHEID	0° tot 20° zwenkbaar, 350° roteerbaar

Elektrische info	
	2 x QPAR51 max.10W
KLASSE	II
DIM TYPE	net-dimbaar (fase afsnijding)

Info lichtbron	
LIGHTSOURCE NAME	GU10

Opmerkingen

lamp not included

Benodigdheden

MINIGRID IN 2 MOUNTING KIT
MINIGRID IN 2 MOUNTING KIT LARGE
CONCRETE PACK MGIT 2

Voor gedetailleerde montage gegevens, consulteer de handleiding : **100015_0000_HAND.pdf**

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
System ceiling	202 71 95 02 - MINIGRID IN 2 MOUNTING KIT	Required

DELTALIGHT

MINIGRID IN TRIMLESS 2 HI LED

100015 0000 W-W

	Plasterboard	202 71 95 02 - MINIGRID IN 2 MOUNTING KIT	Required
	Stucanet	202 71 95 02 - MINIGRID IN 2 MOUNTING KIT	Required
		202 71 95 02L - MINIGRID IN 2 MOUNTING KIT LARGE	Required
	Concrete	202 71 96 02 - CONCRETE PACK MGIT 2	Required
	Concrete + plaster	202 71 95 02L - MINIGRID IN 2 MOUNTING KIT LARGE	Required
	Lintel + plaster	202 71 95 02L - MINIGRID IN 2 MOUNTING KIT LARGE	Required
	Hollow-core slab	202 71 96 02 - CONCRETE PACK MGIT 2	Required
	Hollow-core slab + plaster	202 71 95 02L - MINIGRID IN 2 MOUNTING KIT LARGE	Required
	Stretched ceiling	15212 0130 - MOUNTING KIT MINIGRID IN 2 CSC	Required

VERVOLLEDIG UW SPECIFICATIE

Beton doos voor zichtbeton



202 71 96 02 CONCRETE PACK MGIT 2

Uitsparingsmaat (mm): 260 x 160

Montage kit



202 71 95 02 MINIGRID IN 2 MOUNTING KIT

Uitsparingsmaat (mm): 130 x 233

202 71 95 02L MINIGRID IN 2 MOUNTING KIT LARGE

Uitsparingsmaat (mm): 200 - 100 - 200

DELTALIGHT

MINIGRID IN TRIMLESS 2 HI LED

100015 0000 W-W

Montage kit spanplafond



15212 0130 MOUNTING KIT MINIGRID IN 2 CSC

Notes: