
DELTALIGHT

SPM - CONNECTOR 48V - 180°

REFERENCE 420 99 01



View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
INFORMATION	48V-DC max.200W / CONNECTOR Max.50m

Electrical info	
CERTIFICATES	UL

For detailed installation instructions, please consult the manual : **420_99_01_HAND.pdf**

WHERE USED

420 20 10 00	SPM20 - PROFILE 1m
420 20 20 00	SPM20 - PROFILE 2m
420 20 30 00	SPM20 - PROFILE 3m
420 26 10 00	SLM26 - PROFILE 1m
420 26 20 00	SLM26 - PROFILE 2m
420 26 30 00	SLM26 - PROFILE 3m
420 52 10 00	SPM52 - PROFILE 1m
420 52 20 00	SPM52 - PROFILE 2m
420 52 30 00	SPM52 - PROFILE 3m
23301 0000	SPM20 - PROFILE
23358 0000	SLM26L - PROFILE
23358 0010	SLM26L - PROFILE 1m
23358 0020	SLM26L - PROFILE 2m
23358 0030	SLM26L - PROFILE 3m
23359 0000	SLM26H - PROFILE
23359 0010	SLM26H - PROFILE 1m
23359 0020	SLM26H - PROFILE 2m
23359 0030	SLM26H - PROFILE 3m
23374 0000	SLM44 - PROFILE
23374 0020	SLM44 - PROFILE 2m
23374 0030	SLM44 - PROFILE 3m
23375 0000	SLM35R - PROFILE
23375 0010	SLM35R - PROFILE 1m
23375 0020	SLM35R - PROFILE 2m
23375 0030	SLM35R - PROFILE 3m
23397 0000	SPM20 ST - PROFILE
23397 0020	SPM20 ST - PROFILE 2m
23397 0030	SPM20 ST - PROFILE 3m
24413 0000	SPM52 - PROFILE

DELTALIGHT

SPM - CONNECTOR 48V - 180°

420 99 01

Notes: