
DELTALIGHT




SPYCO ON 2 92733 DIM8

REFERENCE 414 353 812 922 ED8 B

AVAILABLE IN
BLACK 414 353 812 922 ED8 B
WHITE 414 353 812 922 ED8 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1081lm // 13,3W // 81lm/W

Requirements

SPY TUBE S

For detailed installation instructions, please consult the manual : **414_353_812_XXX_ED8_HAND.pdf**


DELTALIGHT

SPYCO ON 2 92733 DIM8

414 353 812 922 ED8 B

FINISH YOUR SPECIFICATION

Finish your product

	**414 02 00 B**	SPY TUBE S B	☐
	414 02 00 FBR	SPY TUBE S FBR	☐
	414 02 00 FG	SPY TUBE S FG	☐
	414 02 00 MMAT	SPY TUBE S MMAT	☐
	414 02 00 SG	SPY TUBE S SG	☐
	414 02 00 W	SPY TUBE S W	☐

Notes: