
DELTALIGHT




# M20/M26H - SPY 52 SOFT 93030 MDL

**REFERENCE** 23398 9040 FG

AVAILABLE IN
**BLACK** 23398 9040 B
**FLEMISH BRONZE** 23398 9040 FBR
**FLEMISH GOLD** 23398 9040 FG
**GOLD COLOURED** 23398 9040 GC
**WHITE** 23398 9040 W



View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-30°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 20° & 45° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | F |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 30° |
| **LED TECHNICS (LIGHT SOURCE)** | 1038lm // 10,2W // 109lm/W |
| **LED TECHNICS (LUMINAIRE)** | 662lm // 11,7W // 56lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

**Options**

DIMMABLE MODULATOR

**Accessories**

HONEYCOMB 42

DELTALIGHT

# M20/M26H - SPY 52 SOFT 93030 MDL

23398 9040 FG

SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual : **23398_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### Current supply

# of Fixtures

Min current | Max current

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**21032 0030** SMART 48 MODULATOR PLUG-IN WD — 16


**Dimtype: WDL = wireless dimmable**

### SMART 48

# of Fixtures


Min current | Max current

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 16

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 16

**Dimtype: WDL = wireless dimmable**

### LED power supplies


# of Fixtures

Min current | Max current

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


# M20/M26H - SPY 52 SOFT 93030 MDL

23398 9040 FG





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 8

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 20


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 8

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 17


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**


## Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B





**19810 0020** LINEAR SPREAD LENS 42




**19810 0030** SPREAD LENS 42





**19810 0040** SOFTENING LENS 42




**19810 0050** GLASS SBL 42

# M20/M26H - SPY 52 SOFT 93030 MDL

23398 9040 FG




**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

## Finish your product




**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

## Replaceable reflector / lens




**19810 0180** SPY 52 REFLECTOR 20°




**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°


# M20/M26H - SPY 52 SOFT 93030 MDL

23398 9040 FG


## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H profile


Available Colours





**23359 0000** SLM26H - PROFILE




**23359 0010** SLM26H - PROFILE 1m




**23359 0020** SLM26H - PROFILE 2m




**23359 0030** SLM26H - PROFILE 3m

### SPLITLINE M20 ST profile

Available Colours




**23397 0000** SPM20 ST - PROFILE





**23397 0020** SPM20 ST - PROFILE 2m





**23397 0030** SPM20 ST - PROFILE 3m

### SPLITLINE M20 profile

Available Colours




**420 20 10 00** SPM20 - PROFILE 1m





**420 20 20 00** SPM20 - PROFILE 2m


DELTALIGHT

# M20/M26H - SPY 52 SOFT 93030 MDL

23398 9040 FG




**420 20 30 00** SPM20 - PROFILE 3m




**23301 0000** SPM20 - PROFILE B

Notes: