



LOGIC 190 R OK 93026 DIM5

30216 9325 INOX

AVAILABLE IN
INOX 30216 9325 INOX



 [View on website](#)



General info

| | |
|---|---|
| LOCATION | outdoor |
| INSTALLATION | Floor Recessed |
| CUTOUT SHAPE/SIZE (MM) | round - BOX |
| RECESSED DEPTH (MM) | 190 |
| INGRESS PROTECTION | IP67 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK10 |
| WEIGHT (KG) | 2 |
| ADJUSTABILITY | 0° to 25° swiveling |
| INFORMATION | 9 x LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC INCL.BEAM LENS 26° INCL.1 x CABLE H07 RN-F 5 x 1mm ² 0,5m INCL.IP68 CONNECTOR 5P ESG 10mm max.500kg |

Electrical info

| | |
|---------------------|--------------------|
| ELECTRICAL | 110-240V / 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI |
| ENERGY CLASS | E |
| CERTIFICATES | CB, ENEC, EPD, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 12,6W / CRI>90 (R9: 64) / 3000K / 1604lm |
| TM-30 VALUES | Rf: 92 / Rg: 99 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 150000 |
| BEAMANGLE | 26° |
| LED TECHNICS (LIGHT SOURCE) | 1604lm // 12,6W // 126lm/W |
| LED TECHNICS (LUMINAIRE) | 1088lm // 14,5W // 75lm/W |

Requirements

LOGIC 190 R BOX

Options

LOGIC 190 ANTI VANDAL SCREWS 2 PCS

DELTALIGHT


LOGIC 190 R OK 93026 DIM5

30216 9325 INOX

For detailed installation instructions, please consult the manual : [30216_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




30210 0010 LOGIC 190 R BOX

Cutout dimension (mm): 300 x 230




Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P



Other



30210 0020 LOGIC 190 ANTI VANDAL SCREWS 2 PCS



Notes: