





## SPIX M PIN 92730

29712 9230 PGR

AVAILABLE IN  
**ANTHRACITE** 29712 9230 N  
**PINE GREEN** 29712 9230 PGR



 [View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Surface mounted
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK05
<b>WEIGHT (KG)</b>	0.8
<b>INFORMATION</b>	LENS FL-30° INCL.1 x CABLE H05 RN-F 2 x 1 mm <sup>2</sup> 2m EXCL.LED POWER SUPPLY 350-700mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	G
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 3,9-8,2W / CRI>90 (R9: 56) / 2700K / 385-677lm
<b>TM-30 VALUES</b>	rf: 91 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG2 (threshold 0,6m)
<b>LM80</b>	L90B10 > 41000
<b>BEAMANGLE</b>	30°
<b>LED TECHNICS (LIGHT SOURCE)</b>	677lm // 8,2W // 83lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	454lm // 9,4W // 48lm/W

### Requirements

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

### Options

CBOX  
 IP68 CONNECTION KIT  
 IP68 CONNECTOR 3P

### Accessories

KAP STRIPER

# DELTALIGHT

## SPIX M PIN 92730

29712 9230 PGR

For detailed installation instructions, please consult the manual : [29712\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30

# DELTALIGHT

## SPIX M PIN 92730

29712 9230 PGR



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



**300 48 700 ED1** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1

3



Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 700 ED5** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

3



Dimtype: DALI

Cutout dimension (mm): 45




**300 48 700 MDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL

3



Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 700 WDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL

3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

3 | 3 | 3



Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

6(6) | 6(6) | 6(4)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 4(2) | 3(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 72




**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3 | 3



Dimtype: 1-10V or DALI or push button



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

4(3) | 4(2) | 3(1)




Dimtype: DALI

Cutout dimension (mm): 72

# DELTALIGHT

## SPIX M PIN 92730

29712 9230 PGR



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10) | 9(6) | 7(4)



**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**



**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 3(2) | 2(1)



**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3) | 3(2) | 2(1)



**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

5->7 | 4->7 | 4->6 | 3->6



**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER

2->3 | 3 | 3



**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

4 | 4 | 4



**Dimtype: 1-10V**

**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

4 | 4 | 4



**Dimtype: DALI**

**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

6(6) | 5(5) | 5(4)



**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

4 | 4 | 4



**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**



**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2




**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**

# DELTALIGHT

## SPIX M PIN 92730

29712 9230 PGR




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**




**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

2->2 | 2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

3->4 | 3->4

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 | 3 | 2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0490** LED POWER SUPPLY 700mA-DC / 30W IP68

3(1)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

4(2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 30**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 30**



**21032 0315** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 30**


# DELTALIGHT

## SPIX M PIN 92730

29712 9230 PGR

### Waterproof connection parts


---



**216 12 00** CBOX

Cutout dimension (mm): 142 x 142

---




**216 12 01** IP68 CONNECTION KIT



**216 12 02** IP68 CONNECTOR 3P

### Light altering devices

---



**223 00 10 B** KAP STRIPER B

Notes: