



LOGIC LINEAR ON 880 94025 DIM5

30835 9425 A

AVAILABLE IN


ALU GREY 30835 9425 A

BLACK 30835 9425 B

FLEMISH BRONZE OUTDOOR 30835 9425 FBRX

ANTHRACITE 30835 9425 N

WHITE 30835 9425 W



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2
INFORMATION	16 x LENS FL-25° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 64) / 4000K / 3898lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	3898lm // 28,8W // 131lm/W
LED TECHNICS (LUMINAIRE)	3226lm // 33,1W // 97lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING SET IP68

LOGIC LINEAR ON 880 94025 DIM5

30835 9425 A

For detailed installation instructions, please consult the manual : [30835_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0390 LED POWER SUPPLY 48V-DC / 90W

Dimtype: non-dimmable

Cutout dimension (mm): 75

2

Fixation components



30810 0040

LOGIC LINEAR 880 BOX EXTEND

30810 0040 INOX WALL BRACKET SET 60 INOX

30810 0040 N

WALL BRACKET SET 60 N




30810 0050 INOX

WALL BRACKET SET 100 INOX

30810 0050 N

WALL BRACKET SET 100 N



30810 0060 INOX

WALL BRACKET SET 200 INOX

30810 0060 N

WALL BRACKET SET 200 N

DELTALIGHT

LOGIC LINEAR ON 880 94025 DIM5

30835 9425 A



30810 0070 INOX FLOOR BRACKET SET INOX

☐

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m

☐

30810 0090 IP68 CABLE + CONNECTOR 5P - 2m

☐

30810 0110 THROUGH WIRING SET IP68 880

☐

Notes: