
DELTALIGHT




SUPER-OH! XS 25 DIM8

REFERENCE 308 21 02 83 ED8 B

AVAILABLE IN
BLACK 308 21 02 83 ED8 B
WHITE 308 21 02 83 ED8 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 13,5W / CRI>80 / 3000K / 1470lm
LED TECHNICS (LIGHT SOURCE)	1470lm // 13,5W // 109lm/W
LED TECHNICS (LUMINAIRE)	691lm // 16W // 45lm/W

For detailed installation instructions, please consult the manual : **308_21_02_XX_ED8_HAND.pdf**

FINISH YOUR SPECIFICATION

Miscellaneous control equipment

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

DELTALIGHT

SUPER-OH! XS 25 DIM8


308 21 02 83 ED8 B



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



300 90 126 FALLING EDGE DIMMER 200W DIM2 16

Dimtype: DALI or push button

Cutout dimension (mm): 67

Notes: