



INFORM SQ P200-4 DOWN 94067

25515 9420 B-B



AVAILABLE IN

BLACK-BLACK 25515 9420 B-B

BLACK-FLEMISH GOLD 25515 9420 B-FG

WHITE-BLACK 25515 9420 W-B

WHITE-WHITE 25515 9420 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 400/600mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 7-11,2W / CRI>90 (R9: 50) / 4000K / 1114-1610lm)
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	3220lm // 22,4W // 144lm/W
LED TECHNICS (LUMINAIRE)	2811lm // 25,8W // 109lm/W

Requirements

INFORM SQ POWERBOX 50W (DIM5)

INFORM POWER SUPPLY 25W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : [25515_XXX0_HAND.pdf](#)

INFORM SQ P200-4 DOWN 94067

25515 9420 B-B

FINISH YOUR SPECIFICATION

Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0010 B INFORM SQ POWERBOX 50W B

1

Dimtype: non-dimmable

25510 0010 W INFORM SQ POWERBOX 50W W

1



25510 0015 B INFORM SQ POWERBOX 50W DIM5 B

1

Dimtype: DALI

25510 0015 W INFORM SQ POWERBOX 50W DIM5 W

1


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0395 INFORM POWER SUPPLY 25W DIM5

1

Dimtype: DALI



25510 0440 INFORM POWER SUPPLY 25W

1

Dimtype: non-dimmable

Electric connection parts

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

INFORM SQ P200-4 DOWN 94067

25515 9420 B-B



15225 0350 B SUSPENSION + CONNECTION ST B

2 needed

☐

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W

2 needed

☐

Notes: